



LEGIO.mini tap m



LEGIO.mini shower m



LEGIO.mini tap and shower medical

The LEGIO.mini tap and mini shower medical are the ideal solution for the tap application in case of microbiologically contaminated tap water to prevent bacterial infectious diseases of immunocompromised patients. The safety of patients and employees of medical facilities as well as the safety of use for users in other facilities are the main goal of LEGIO.mini medical. The medical filter is used to prevent infectious diseases of immunosuppressed and immunocompromised patients caused by water associated bacteria in tap water.

Advantages of LEGIO.mini

- Proven efficacy in the retention of legionella and other bacteria (tested after ASTM F838)
- Point-of-use filter with 0,15µm hollow fiber membrane
- CE-marked medical product of class I
- Certified qualitymanagementsystem after ISO 13485
- Antibacterial additive in the filter housing to prevent retrograde contamination (tested after ISO 22196)
- Long time of use up to 70 days (depending on the quality of the supply water and frequency of use)
- Minimal overall height, small and compact filter size to ensure uncomplicated use
- Quick installation and exchange without any tools
- Resistant to all common disinfectants
- Traceability through barcode on the filter

Infection control

tap and shower



LEGIO.mini tap and shower medical

Medical filter

Filter specifications & performance data

Model	30.1.100	30.1.200
Туре	LEGIO.mini tap m	LEGIO.mini shower m
Max. Dimensions	Ø 55 mm x 75 mm	Ø 55 mm x 75 mm
Weight (approx.)	70 gr.	70 gr.
Fast coupling	In M24 male or in M22 female	In M24 male or in M22 female
Initial flow rate at 2 bar	ca. 8 l/min.	ca. 8 l/min.
Validated Lifetime	70 days (10 weeks)	70 days (10 weeks)
Pore size	0,15 μm	0,15 μm
Bacterial Retention	LOG > 7	LOG > 7

Materials and technical data of the filter

Filter housing	ABS (acrylonitrile-butadiene-styrene)	
	Antibacterial additive	
Max. Operating Pressure	5 bar	
Max. Operating Temperature	60°C, 75°C for 30 minutes while using	
Chlorine Exposure	in accordance with the drinking water regulation	
Storage & Handling	Keep dry during storage; protect against freezing	
	Handle with care; do not expose to shocks	
	Disinfections of the surface with all common medical surface disinfectants	
	Disposable product, discard as regular waste	
Replacement of filter	Replace the filter when the capacity limit is reached, when the flow rate is	
	reduced or at the latest after 70 days	
Recommendation	Remove LEGIO.mini for thermal disinfection	

The membrane unit was tested by the independent Dutch test laboratory Vitens regarding the bacterial retention after ASTM F838.

LEGIO.mini medical is a medical product of class I and complies with the Regulation (EU) 2017/745 of the European Parliament and the Council on medical devices and other relevant EU legislation. Further information can be found in the validation.

All products and components of LEGIO are subject to strict quality controls. Each product is individually tested for its function and effectiveness.

Disclaimer

The information and data provided in this document are based on our general experience and are believed to be accurate. It is given in good faith and is intended to provide a guide for the selection and use of our products. As the conditions under which our products may be used are beyond our control, this information is not a guarantee of the final performance of the product and we accept no liability in respect of the use of our products. The quality of our products is guaranteed in accordance with our conditions of sale. Existing (industrial, intellectual or other) property rights must be observed.





